VACUUM CIRCUIT BREAKER

ZW32-12


Outdoor type High voltage AC Vacuum circuit breaker



Description

ZW32-12 Outdoor high voltage vacuum circuit breaker is the outdoor high voltage switch equipment with three phase AC50Hz, Rated voltage of 12kV, it is suitable for breaking and closing the load current, overload current and shirt-circuit current of the urban or rural power distribution system.

Model No. and its implication



Main technical parameter

	Unit	ZW32-12/630-20	ZW32-12/630-25
Rated voltage		12	
Rated current		630 1250	
Rated short-circuit breaking current		20	25
Rated short-circuit closing current(peak)		50	63
Rated peak withstand current		50	63
Rated short-time withstand current		20	25
Rated short-circuit continuous time		4	
Lightning impulse withstand voltage (peak)	kV	Interphase, to ground 75, fracture85	
1min power frequency withstand voltage		Interphase, to ground 42, fracture48	
Rated operation sequency		O-0.3s-CO-180s-CO(Electric operation)	
Rated short-circuit current breaking time		30	
Electrical life		10000	
Rated operating voltage (Opening and closing coil)		DC220,110,AC220	
Moving and fixing contacts allowable accumulated thickness		3	
Rated current of over-current tripping		5	
Current ration of current transformer (regular)		200/5 400/5 630/5	
	closing current(peak) and current athstand current continuous time Lightning impulse withstand voltage (peak) 1min power frequency withstand voltage quency current breaking time Itage ag coil) ontacts allowable ess er-current tripping	kV A breaking current closing current(peak) and current ithstand current continuous time Lightning impulse withstand voltage (peak) 1min power frequency withstand voltage quency current breaking time Cycles Itage and coil) contacts allowable ess er-current tripping KA kA kA kA kA kA kA kA kV min power frequency withstand voltage quency current breaking time Cycles	kV 1 A 630 breaking current 20 closing current(peak)

ZW32-12

Outdoor type High voltage AC Vacuum circuit breaker

		Unit	ZW32-12/630-20	ZW32-12/630-25
Contact opening distance		mm	9±1	
Contact overstroke			2+1	
Average opening speed		m/s	1.2±0.2	
Average closing speed			0.6±0.2	
Opening time			15~50	
Closing time		ms	25~80	
Closing tripping time			≤2	
Three phase opening and closing synchronism			≤2	
Each phase circuit DC resistance		$m\Omega$	≤80	
Energy storage motor	Rated voltage	V	DC/AC 220	
	Rated power	W	70	
	Energy storage time	S	≤	8
Weight		kg	100	

Overall and installation dimensions




Diagram 1 ZW32-12 Outdoor high voltage vacuum circuit breaker

VACUUM CIRCUIT BREAKER

ZW32-12

Outdoor type High voltage AC Vacuum circuit breaker




Diagram 2 ZW32-12(G) Outdoor high voltage vacuum circuit breaker




Diagram 3 ZW32-12(G) Outdoor high voltage vacuum circuit breaker installation dimension